

DATA SHEET

SURFACE TREATMENTS

PRODUCTS

NOVATOP SWP, EASY BOARD

We offer various coating options according to the type of supplier in the design of **STANDARD** or **ON DEMAND**. Other surface treatment options are available only on the individual demand.

TYPES OF SURFACE TREATMENT:

Water-soluble glazing paint, UV stable

- Very low VOC (volatile organic compounds) values
- Highly transparent effect, stabilizes the natural appearance of wood
- Resistance to colour changes due to UV radiation.
- For more information, see the manufacturer's technical data sheets

ADLER LIGNOVIT INTERIOR UV 100					
Coating	Visual / non-visual side Number of layers		Execution	Application	
				Interior	Covered exterior
Basic	1/0	1/1	STANDARD	YES	NO
Final	-	2/1	ON DEMAND	YES	NO
SHADES					
NATUR		ZUGSPITZ		MONT BLANC	
Natural		White with a smaller proportion of pigment		White with a greater proportion of pigment	
TECHNICAL PARAMETERS					
Primer		1 layer applied manually with a roller, without edge protection		Amount 120–150 g/ m²	
Final surface Visual/non-visual		2 layers of spray paint with intermediate sanding, without edge protection / 1 layer of spray paint		Amount 2x 80-90 g/ m²	
Manufacturer's technical data sheet at: https://www.adler-lacke.com/					

SHERWIN-WILLIAMS LACROMA CLEAR 10					
Coating	Visual / non-visual side Number of layers		Execution	Application	
				Interior	Covered exterior
Basic	1/0	1/1	ON DEMAND	YES	NO
Final	-	2/1	STANDARD	YES	NO
SHADES					
NATUR		VENUS		POLARIS	
Natural		White with a smaller proportion of pigment		White with a greater proportion of pigment	
TECHNICAL PARAMETERS					
Primer		1 layer applied manually with a roller, without edge protection		Amount 70–90 g/ m ²	
Final surface Visual/non-visual		2 layers of spray paint with intermediate sanding, without edge protection / 1 layer of spray paint		Amount 65–75 g/ m ²	
Manufacturer's technical data sheet at: https://www.sherwin-williams.com/					

DATA SHEET

SURFACE TREATMENTS

KOCH & SCHULTE H420 LEONARDO® DESIGNER FINISH					
Coating	Visual / non-visual side Number of layers		Execution	Application	
				Interior	Covered exterior
Basic	1/0	1/1	ON DEMAND	YES	YES
SHADES					
Natural		White with a smaller proportion of pigment		White with a greater proportion of pigment	
TECHNICAL PARAMETERS					
Primer		1x layer, without edge protection		Amount 100–150 g/ m²	
Manufacturer's technical data sheet at: https://www.kochundschulte.de/					

Manufacturer's technical data sheet at: <https://www.kochundschulte.de/>

BLENDA NOVA					
Coating	Visual / non-visual side Number of layers		Execution	Application	
				Interior	Covered exterior
Basic	1/0	–	ON DEMAND	YES	NO
SHADES					
White with a smaller proportion of pigment					
TECHNICAL PARAMETERS					
Primer	1x layer, without edge protection			Amount 100 – 125 g/m ²	

Manufacturer's technical data sheet at: <https://www.knuchel.swiss/>

REMMERS INDULINE LW-716					
Coating	Visual / non-visual side Number of layers		Execution	Application	
				Interior	Covered exterior
Basic	–	1/1	ON DEMAND	NO	YES
SHADES					
Pohledová strana – bílá / nepohledová strana – transparent					
TECHNICAL PARAMETERS					
Primer	1x layer, without edge protection			Amount 100 g/ m ²	

Manufacturer's technical data sheet at: <https://www.remmers.com/>

DATA SHEET

SURFACE TREATMENTS

SAMPLER

Shades of glazes

The colour of the images is for reference only and may differ from the original due to printing.
Shades of glazes from other manufacturers and other colour options are only available upon individual request.

ADLER LIGNOVIT INTERIOR UV 100



Natur



Zugspitz



MontBlanc

SHERWIN-WILLIAMS LACROMA CLEAR 10



Natur



Venus



Polaris

DATA SHEET

SURFACE TREATMENTS

PRODUCTS

NOVATOP ACOUSTIC

We offer various coating options according to the type of supplier in the design of **STANDARD** or **ON DEMAND**. Other surface treatment options are available only on the individual demand.

TYPES OF SURFACE TREATMENT:

Water-soluble glazing paint, UV stable

- Very low VOC (volatile organic compounds) values
- Highly transparent effect, stabilizes the natural appearance of wood
- Resistance to colour changes due to UV radiation.
- For more information, see the manufacturer's technical data sheets

ADLER LIGNOVIT INTERIOR UV 100				
Coating	Number of layers	Execution	Application	
			Interior	Covered exterior
Basic	1	STANDARD	YES	NO
Final	2	ON DEMAND	YES	NO
SHADES				
NATUR		ZUGSPITZ	MONT BLANC	
Natural		White with a smaller proportion of pigment	White with a greater proportion of pigment	
TECHNICAL PARAMETERS				
Primer		1 layer applied manually with a roller, without edge protection	Amount 120–150 g/ m²	
Final surface Visual/non-visual		2 layers of spray paint with intermediate sanding, without edge protection	Amount 2x 80-90 g/ m²	
Manufacturer's technical data sheet at: https://www.adler-lacke.com/				

SHERWIN-WILLIAMS LACROMA CLEAR 10				
Coating	Number of layers	Execution	Application	
			Interior	Covered exterior
Basic	1	ON DEMAND	YES	NO
Final	2	STANDARD	YES	NO
SHADES				
NATUR		VENUS	POLARIS	
Natural		White with a smaller proportion of pigment	White with a greater proportion of pigment	
TECHNICAL PARAMETERS				
Primer		1 layer applied manually with a roller, without edge protection	Amount 70–90 g/ m ²	
Final surface Visual/non-visual		2 layers of spray paint with intermediate sanding, without edge protection	Amount 65–75 g/ m ²	
Manufacturer's technical data sheet at: https://www.sherwin-williams.com/				

DATA SHEET

SURFACE TREATMENTS

SAMPLER

Shades of glazes

The colour of the images is for reference only and may differ from the original due to printing.
Shades of glazes from other manufacturers and other colour options are only available upon individual request.

ADLER LIGNOVIT INTERIOR UV 100



Natur



Zugspitz



MontBlanc

SHERWIN-WILLIAMS LACROMA CLEAR 10



Natur



Venus



Polaris